

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

[10191/1961]

METHOD AND DEVICE FOR DETERMINING A SPEED VARIABLE
OF AT LEAST ONE DRIVEN WHEEL OF A MOTOR VEHICLE

[Background Information]

] FIELD OF THE INVENTION

5 The present invention relates to a method and a device for determining a variable [which describes] describing the speed of at least one driven wheel of a motor vehicle[. Using the method and the device,] for ascertaining variables [which describe] describing the respective wheel speeds[are ascertained] for the remaining driven wheels of the motor vehicle[. Furthermore,] and for determining a variable [is determined which describes] describing the output rpm of a transmission of the motor vehicle.[

10] The present invention also relates to a control unit for a traction control system or a vehicle-dynamics control system of a motor vehicle. To control the drive slip and/or the vehicle dynamics, the control unit determines a variable [which describes] describing the speed of at least one driven wheel of the motor vehicle. Variables describing the respective wheel speeds for the remaining driven wheels of the motor vehicle, and a variable describing the output rpm of a transmission of the motor vehicle are available to the control unit.[

20 Furthermore, t] The present invention also relates to a memory element for a control unit of a traction control system or a vehicle-dynamics control system of a motor vehicle. The memory element [is constructed in particular as] may be a read-only memory, a random-access memory or a flash memory. Stored in the memory element is a computer program [which] that is executable on a computing element, [particularly

30 on] including a microprocessor.[

EL 24450728/45

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

] Finally, the present invention also relates to a computer program [which] that is executable on a computing element, [particularly on] including a microprocessor.

5

[Related Art

Methods] BACKGROUND INFORMATION

10

It is believed that various methods and devices for determining a speed variable of at least one driven wheel of a motor vehicle are [known in various specific embodiments from the related art] available.

15

Thus, for example, [the] German Published Patent Application No. 196 108 64 [A1 describes] discusses a method and a device for determining a wheel speed. In that case, the rotational speed of at least one of two wheels of an axle is determined. To that end, a first variable representing the average rotational speed of the two wheels, and a second variable representing the vehicular speed are ascertained. The wheel speed is[] determined as a function of a comparison of a threshold value and of the difference between a value derived from the first variable and a value derived from the second variable[, to a threshold value]. Upon falling below the threshold value, the rotational motion of the one wheel is determined at zero, and upon exceeding the threshold value, the rotational motion is determined at a value different from zero.

25

[

30

The ascertainment of]

It is believed, however, that ascertaining the wheel speed [known from

DE 196 108 64 A1] as above may ha[s]ve the disadvantage that a variable describing the vehicular may be speed is necessary.

35

To be able to determine a precise wheel speed, it is believed

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

that a precise determination of the vehicular speed [is] may be required. This may demand[s] either very accurate estimation methods [which determine] for determining the vehicular speed, for example, on the basis of the wheel speeds, or else special
5 sensors for detecting the wheel speeds, which, however, may
require too much effort and [are] therefore may be costly. If
the vehicular speed is determined as a function of the wheel
speeds, only wheel speeds are available as initial quantities, based on which the rotational speed of at least one of two
10 wheels of an axle is determined. Because of this, a systematic error [can possibly] may develop, since a further variable
which is independent of the wheel speeds [does] may not go into
the determination of the rotational speeds.

[The] In German Published Patent Application No. 197 26 743 [A1 describes] is discussed a method and a device for automatically determining a differential ratio between a transmission of a motor vehicle and the wheels. In that case, a variable describing the speed of at least one wheel, and the output rpm
20 of the transmission are determined. Furthermore, a driving-state variable describing the driving state of the motor vehicle is ascertained. If an essentially steady[] driving state exists, the variable describing the differential ratio is determined as a function of the variable describing
25 the wheel speed, and the output rpm of the transmission.

[The] An object of an exemplary embodiment and/or exemplary method of the present invention is to [improve the ascertainment of] ascertain a variable describing the wheel
30 speed of at least one driven wheel of a motor vehicle. In particular, it is believed that the [intention is to] foregoing provide[a possibility of]s for making a reliable variable describing the speed magnitude of the wheel available to a traction control system or a vehicle-dynamics control system
35 of a motor vehicle, in spite of the failure of a speed sensor

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

arranged at one of the wheels.

[To achieve this objective, starting from the method of the type indicated at the outset, the present invention proposes that] In particular, for the at least one driven wheel, the variable describing the speed may be determined as a function of the variables [which describe] describing the respective wheel speeds of the remaining driven wheels, and as a function of the variable [which describes] describing the transmission output rpm.

[Summary of the Invention

SUMMARY OF THE INVENTION

The driven wheels of a motor vehicle [are generally] may be fixedly coupled via a differential to the output end of a transmission[. This holds true], including for[the] front-wheel drive (FWD) and [a] for rear-wheel drive (RWD). In the case of [an] all-wheel drive (AWD), there [is] may be such a fixed coupling only when no slip-encumbered components, such as a viscous coupling, are integrated into this part of the drive train. This fixed coupling exists in the case of all-wheel-drive vehicles with open differentials.

The variable describing the speed of at least one driven wheel [can easily] may be determined according to the exemplary method of the present invention, given a fixed coupling of the driven wheels to the output end of the transmission. To that end, the known variables [which describe] describing the respective wheel speeds of the remaining driven wheels are [utilized] used. In addition, the variable describing the transmission output rpm is [utilized] used. [As a rule, t] These variables are available in a control unit for the transmission[or] for a traction control system [or] or for a vehicle-dynamics control system, and do not have to be determined separately.

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

The transmission output rpm is ascertainable with low expenditure and high accuracy. The determination is carried out, for example, by a speed sensor mounted at a suitable location on the transmission.

5

The exemplary method of the present invention can be used to check the performance reliability of wheel-speed sensors of the motor vehicle. For that purpose, the speed variable can be determined in succession for all wheels of the motor vehicle according to the exemplary method of the present invention and compared to the speed variable detected by the wheel-speed sensor to be checked.

10

[With] Using the [aid of the] exemplary method of the present invention, [an equivalent] a corresponding or comparable quantity can be formed for a wheel speed or wheel rotational speed not directly available. For example, a directly determined variable [is] may not be available when a wheel-speed sensor is defective. Thus, using the exemplary method of the present invention, a reliable speed variable of the wheel can be made available in spite of the failure of a wheel-speed sensor. The system availability of a motor vehicle [is] may thereby be increased, particularly in the event of a wheel-speed sensor malfunction. That is to say, the vehicle may continue[s] to be operable in spite of the failure or defect of a wheel-speed sensor. In particular, a reliable quantity describing the speed variable of the wheel can be made available to a traction control system or a vehicle-dynamics control system of a motor vehicle in spite of a malfunction of a wheel-speed sensor. In comparison to previously used traction control systems or vehicle-dynamics control systems, when using the exemplary method of the present invention, it is believed that a system need no longer be switched into the passive state in response to a detected fault in a wheel-speed sensor. The system should continue[s]

15

20

25

30

35

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

to be available and fully operative, in spite of such a fault or failure of the wheel-speed sensor[,].

Such traction control systems or vehicle-dynamics control systems are [known]discussed, for example, [from]in the publication

"FDR - Die Fahrdynamikregelung von Bosch" [[]](VDC - The Vehicle Dynamics Control of Bosch[[]]) appearing in the Automobiltechnischen Zeitschrift (ATZ) 96, 1994, issue 11, on pp. 674 through 689. The yaw rate of a motor vehicle is controlled using a device [described there]discussed in that reference. To control the yaw rate of the vehicle, the measured yaw rate is compared to a setpoint value for the yaw rate. Using this comparison, a system deviation of the yaw rate is determined, as a function of which driver-independent, wheel-individual braking interventions and/or engine interventions are carried out. [P]What may be primarily by the driver-independent, wheel-individual braking interventions, a yaw moment is exerted on the vehicle, by which the actual yaw rate comes closer to[. In] the [meantime, t]setpoint value. The [described]foregoing vehicle-dynamics control system is [now]also[widely] referred to as ESP (Electronic Stability Program). The contents of the publication "FDR - Die Fahrdynamikregelung von Bosch" are [herewith intended to be included ibidem in the description and thus to be part of the description.

In summary, it can be said that: An equivalent]incorporated by reference.

In summary, an equivalent (that is, corresponding or comparable) quantity is determined for the speed or the rotational speed of a motor-vehicle wheel having a failed wheel-speed sensor using the sensed rotational speed or speed

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

of the remaining wheels and the output rpm of a transmission.
The transmission [is preferably]may be an automatic
transmission. However, the exemplary method of the present
invention functions just as well with a manually shifted
5 transmission having a manual or an automatic actuation.

According to [one advantageous further development]another
exemplary method of the present invention, a variable specific
to the wheel plane and describing the output speed is
10 determined as a function of the transmission output rpm[; and
f)]. For the at least one driven wheel, the variable
describing the speed is determined as a function of the
variables [which describe]describing the respective wheel
speeds of the remaining driven wheels, and as a function of
15 the variable [which describes]describing the output speed.

According to [a best mode]another exemplary embodiment of the
present invention, the variable specific to the wheel plane
and describing the output speed is determined [with the aid
20 of]using the equation of:

$$V_{output} = \frac{\pi}{30} \cdot \frac{R_{wheel}}{I_{Diff}} \cdot n_{output},$$

where R_{wheel} [being]is the radius of the driven wheels and I_{Diff}
[being]is the effective differential ratio(s).

25 For a motor vehicle having all-wheel drive, the variable
describing the speed for the at least one driven wheel [is]may
be advantageously determined [with the aid of]using the
equation of:

$$V_{wheelDef} = 4 \cdot V_{output} - \sum_{i=1}^3 V_{wheeli}$$

30 For a motor vehicle having front-wheel drive or rear-wheel

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

drive, the variable describing the speed for the at least one driven wheel [is] may be advantageously determined according to the equation:

5
$$V_{\text{wheelDef}} = 2 \cdot V_{\text{output}} - V_{\text{wheel}}$$

where V_{wheel} [being] is the wheel speed of the driven wheel whose wheel speed is not to be determined, that is to say, whose wheel-speed sensor is not defective.

10 [As a further means for achieving the objective] Further, starting from the device indicated at the outset, the exemplary device determines the variable describing the speed for the at least one driven wheel as a function of the variables describing the respective wheel speeds of the remaining driven wheels, and as a function of the variable
15 describing the transmission output rpm.

20 According to another exemplary embodiment of the present invention, the device includes an apparatus, arrangement or structure for performing the exemplary method according to the present invention.

25 Further, starting from the [device of the type] control unit indicated at the outset, [it is proposed that] the [device] exemplary control unit determines the variable describing the speed for the at least one driven wheel as a function of the variables [which describe] describing the respective wheel speeds of the remaining driven wheels, and as a function of the variable [which describes] describing the
30 transmission output rpm.

According to [one advantageous further development] another exemplary embodiment of the present invention, [it is proposed

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

that]the apparatus, arrangement or structure for performing the [device have means for carrying into effect the]exemplary method according to the [invention.

5 As a further means for achieving the objective of the present invention, starting from the control unit of the type indicated at the outset, it is proposed that the control unit determine the variable describing the speed for the at least one driven wheel as a function of the variables which describe
10 the respective wheel speeds of the remaining driven wheels, and as a function of the variable which describes the transmission output rpm.

According to one advantageous further development of the present invention, it is proposed that means for carrying into effect the method according to the invention be]present
invention is implemented in the control unit.

[Particularly significant is the implementation of the]The exemplary method according to the present invention may be implemented in the form of a memory element that is provided for a control unit of a traction control system or a vehicle-dynamics control system of a motor vehicle. In this context, a computer program that is executable on a computing
20 element, in particular on a microprocessor, and that is suitable for carrying out or performing the exemplary method according to the present invention, is stored at, in or on the memory element. In this case, therefore, the exemplary embodiment of the present invention is realized by way of a
25 computer program stored at, in or on the memory element, so that this memory element, as provided with the computer program, constitutes the exemplary embodiment of the present invention in the same way as the exemplary method for whose accomplishment the computer program is suitable. In
30 particular, an electrical storage medium, for example, a
35

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

read-only memory, a random-access memory, or a flash memory, can be used as the memory element.

The exemplary embodiment of the invention also relates to a computer program that is suitable for carrying out the exemplary method according to the present invention when it is executed on a computing element, in particular on a microprocessor. In this context, [it is particularly preferred if]the computer program [is]may be stored [on]in a memory element, in particular [on]in a flash memory.

[Brief Description of the Drawing

Additional features, possibilities for use, and advantages of the present invention come to light from the following description of exemplary embodiments of the present invention represented in the Drawing. In this context, all of the described or represented features, alone or in any combination, form the subject matter of the present invention, regardless of their combination in the patent claims or their antecedents, as well as regardless of their formulation and representation in the Specification and Drawing, respectively.

Figure 1]BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a block diagram of [a]an exemplary device according to the present invention[; and].

Figure 2[] shows a flow chart of [the]an exemplary method according to the present invention.

[Description of the Exemplary Embodiments

] DETAILED DESCRIPTION

Figure 1 shows a drive train of a motor vehicle having four wheels 1, 2, 3, 4. The direction of travel of the motor vehicle is indicated by an arrow 20. The front wheels

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

(front-wheel drive, FWD), the rear wheels (rear-wheel drive, RWD) or the front and rear wheels (all-wheel drive, AWD) can be driven in the motor vehicle. The driven wheels of the FWD and of the RWD [are generally] may be fixedly coupled via a differential to the output end of a transmission 5. In the case of AWD, there is a fixed coupling only when no slip-encumbered components, such as a viscous-friction coupling (so-called viscous coupling), are integrated into this part of the drive train. This fixed coupling [exists] is provided in[the case of] all-wheel-drive vehicles with open differentials. As can be seen in Figure 1, the single-axle-driven motor vehicles, i.e., FWD and RWD motor vehicles, have two differentials 6, 7. All-wheel drive, i.e., AWD vehicles, have three differentials 6, 7, 8.

Both front wheels 1, 2 of the vehicle have wheel speeds V_{wheel1} and V_{wheel2} . Both rear wheels have wheels speeds V_{wheel3} and V_{wheel4} . The speeds of wheels 1, 2, 3, 4 are determined from rotational speeds n_{wheel1} , n_{wheel2} , n_{wheel3} , n_{wheel4} and from radius R_{wheel} of wheels 1, 2, 3, 4. Instead of radius R_{wheel} , it is also possible to [utilize] use the diameter of wheels 1, 2, 3, 4. Rotational speeds n_{wheel1} , n_{wheel2} , n_{wheel3} , n_{wheel4} of wheels 1, 2, 3, 4 are detected by speed sensors 9, 10, 11, 12 [which] that are arranged in the area of wheels 1, 2, 3, 4. Transmission 5 is an automatic transmission.

Transmission 5 is linked via a controller area network (CAN) bus 15, [inter alia] in part, to a control unit 14 of a vehicle-dynamics control system 14[that], which is also [widely known] referred to as ESP (electronic stability program). The design and the functioning method of an ESP is [described in detail] discussed in the publication "*FDR - Die Fahrdynamikregelung von Bosch*", [ibidem, and is herewith intended to be included in the description and thus to be part of the description] which is incorporated by reference.

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

On condition that output rpm n_{output} of automatic transmission 5 is measured by an independent sensor 13 and all driven wheels are coupled in a slip-free manner to the output end of transmission 5, [an equivalent]a quantity for a failed speed sensor 9, 10, 11 or 12 can be formed according to the exemplary method of the present invention. A prerequisite for this is that wheel 1, 2, 3 or 4 having the defective speed sensor is a wheel coupled to transmission 5, thus a driven wheel.

To carry out or perform the exemplary method of the present invention, control unit 14 has a memory element 16 and a computing element, particularly a microprocessor 17. For example, memory element 16 [is constructed as]may be a flash memory. Stored on memory element 16 is a computer program [which]that is executable on microprocessor 17 and that is suitable for implementing the method of the present invention. To control the operating-dynamics stability of the motor vehicle, control unit 14 is supplied with input variable[]s 18 which also include, [inter alia]in part, wheel speeds V_{wheel1} , V_{wheel2} , V_{wheel3} , V_{wheel4} and output rpm n_{output} of transmission 5. From these input variables 18, control unit 14 determines output quantities 19, for example, for controlling an internal combustion engine, a braking system (particularly an ABS braking system) or a steering system (particularly a steer-by-wire steering system) of the motor vehicle.

In the case of an AWD motor vehicle, the [corresponding or comparable (or equivalent)] quantity describing speed V_{wheelDef} of a wheel 1, 2, 3 or 4 having a defective wheel-speed sensor 9, 10, 11 or 12 is determined [with the aid of]using the equation of:

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

$$V_{wheelDef} = 4 \cdot V_{output} - \sum_{i=1}^3 V_{wheeli}$$

where V_{output} [being] is a variable specific to the wheel plane and describing the output speed of transmission 5, which is determined by the equation of:

$$V_{output} = \frac{\pi}{30} \cdot \frac{R_{wheel}}{I_{Diff}} \cdot n_{output}$$

where V_{wheeli} is the rotational speed of the remaining driven wheels whose wheel-speed sensors are in working order. That is [to say], output speed V_{output} is yielded as a function of output rpm n_{output} and a conversion factor for converting revolutions per minute (R/min) into meters per second (m/s). Output speed V_{output} corresponds to the average value of wheel speeds V_{wheeli} of the driven wheels.

In a motor vehicle having front-wheel drive or rear-wheel drive, the [equivalent] corresponding or comparable quantity is determined [with the aid of] using the equation of:

$$V_{wheelDef} = 2 \cdot V_{output} - V_{wheel}$$

where V_{wheel} [being] is the wheel speed of the other driven wheel whose wheel-speed sensor is in working order.

Depending on the type of drive of the motor vehicle, effective differential ratio I_{Diff} can be composed of the ratios of differentials 6, 7 and/or 8. In the case of a FWD, it is composed of the two differential ratios I_{DiffQ} of front differential 6 and $I_{Diffmiddle}$ of middle differential 8, and in the case of a RWD, it is composed of the two differential ratios I_{DiffQ} of rear differential 7 and $I_{Diffmiddle}$ of middle differential 8. In the case of an AWD, all differential ratios I_{DiffQ} , I_{DiffQ} , and $I_{Diffmiddle}$ must be taken into account or combined.

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

In this context, differential ratio I_{Diff} is yielded as the product of the individual differential ratios. Allowance [must possibly] may need to be made for an effective off-road reduction.

5 [In the event] If a wheel-speed sensor 9, 10, 11 or 12 is not in working order, [an] the corresponding or comparable (or equivalent)] quantity [which describes] describing the speed of the wheel can be calculated for the wheel having the defective
10 wheel-speed sensor using the exemplary method of the present invention. Thus, a shutdown of a complete vehicle-dynamics control system or a complete traction control system [is] should no[longer] t be necessary. For example, [it is conceivable to make]an ABS function, i.e., a traction control system which is based solely on braking interventions,
15 [possible] may be provided up to a specific vehicle speed with a defective wheel-speed sensor 9, 10, 11 or 12. The probability of the failure of the complete vehicle [is] should therefore be markedly reduced. This should hold[s] true in particular for off-road vehicles in which external wheel-speed
20 sensors 9, 10, 11, 12 [are] may be subject to particularly high external stress during off-road travel. The shutdown behavior for the ABS case, i.e., the brake-slip control contained in the vehicle-dynamics control, [can] may also be developed more
25 favorably[, as well].

Figure 2 shows a flowchart of the exemplary method according to the present invention. The exemplary method begins in a functional block 30. In the following, it is assumed that the
30 motor vehicle has a front-wheel drive (FWD), and [the intention is to determine an equivalent] a corresponding or comparable quantity describing the speed of wheel 2 must be determined. To that end, in a functional block 31, [first of all] a variable specific to the wheel plane and describing
35 output speed V_{output} of transmission 5 is first determined.

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

Output speed variable V_{output} is determined as a function of transmission output rpm n_{output} according to the following equation:

$$V_{\text{output}} = \frac{\pi}{30} \cdot \frac{R_{\text{wheel}}}{I_{\text{Diff}}} \cdot n_{\text{output}}$$

5 The corresponding or comparable (or equivalent) quantity describing speed $V_{\text{wheelDef}} = V_{\text{wheel2}}$ of wheel 2 is subsequently determined in a functional block 32 according to the following equation:

10

$$V_{\text{wheelDef}} = 2 \cdot V_{\text{output}} - V_{\text{wheel}}$$

15 In this context, V_{wheel} is the speed of wheel 1 having speed sensor 9 in working order. In a functional block 33, the exemplary method of the present invention is then brought to an end.

20 Wheel-speed variable V_{wheelDef} , determined [with] using the [aid of the] exemplary method according to the present invention, is compared to wheel speed V_{wheel2} [which was] detected by speed sensor 10 of wheel 2. If the deviations of the two wheel speeds exceed a specifiable threshold value, a malfunction of speed sensor 10 is assumed. [Naturally, w] Wheel-speed variable V_{wheelDef} [utilized] used with the exemplary method of the present invention can also be [utilized] used as a corresponding or
25 comparable (or equivalent) quantity for wheel speed V_{wheel2} of wheel 2 [in the event] if speed sensor 10 is defective.

MARKED UP VERSION OF SUBSTITUTE SPECIFICATION

[Abstract] ABSTRACT OF THE DISCLOSURE

[

The invention relates to a]A method and a device for
determining a variable describing the speed [(V_{wheelDef})of]at
5 least one driven wheel[(1, 2, 3, 4)] of a motor vehicle. In
this context, variables describing the respective wheel speeds
[(V_{wheeli})]for the remaining driven wheels of the motor vehicle,
and a variable describing the output rpm [(n_{output})]of a
transmission[(5)] of the motor vehicle are determined. To be
10 able to make a reliable variable describing the speed
magnitude of the wheel[(1, 2, 3, 4)] available to a traction
control system or a vehicle-dynamics control system of a motor
vehicle in spite of the failure of a speed sensor [(9, 10, 11,
12)]arranged at one of the wheels,[it is proposed that] the
15 variable describing the speed [(V_{wheelDef})]for the at least one
driven wheel [(1, 2, 3, 4) be]is determined as a function of
the variables [which describe]describing the respective wheel
speeds [(V_{wheeli})]of the remaining driven wheels and as a
function of the variable [which describes]describing the
20 transmission output rpm[(n_{output}).].

[(Figure 1)]

398890